



LEVANTE OR HURRICANE SIDE WIND COVER REMOVAL / REFITTING

Please see the below instructions for removing and fitting a parasol cover for a Side Wind Levante or Hurricane parasol.

If you have any problems, or questions during the change over , please feel free to contact us for advice using the email address at the bottom of the page.

Before starting to remove the cover, make sure that the parasol is in a secure position or is laid down to avoid risking damage to the umbrella or yourself.

To begin the removal, first unscrew the decoration tube connecting the wire from the winch box to the canopy.



Next, release the tilt rope and pull it out of the cleat.



For the next part, you will need an extra pair of hands to assist you. While someone supports the canopy, release the hanging bolt and lift the canopy frame out of the hanging bracket

Lay the canopy frame on a flat surface et. A table top, using a sheet to protect the canopy if possible.

Remove the cover bolts at the end of the ribs, making sure to keep them safe.



Then, working on the metal tube, remove the two side spacers and the through-bolt using an Allen key.

Keep all parts safe for re-assembly.



When all parts are removed from the sides of the tube slide the protective collar up the tube.

We have put some masking tape on the tube, to prevent the wire from damaging the finish.

When there are no obstructions left, remove the cover over the end of the tube.

To refit the parasol, simply reverse the procedure.